

4 INCH LEG RETROFIT KIT KIT #009126SK

TOOLS NEEDED PARTS INCLUDED

- Phillips Screw Driver

- Part #009127 4 Inch Legs
- Part #009103 Rubber Caps

INSTALLATION INSTRUCTIONS

- 1. Unplug unit from outlet. Remove all products from inside the unit and let cool.
- 2. Remove screws from the top cap of the warmer.
- 3. Remove the top cap.
- 4. Remove screws from the water tank cover.
- 5. Remove the water tank cover and water tank.
- 6. Lay the warmer on its front so the door and control panel are facing up. (If you have a two door warmer, either remove the front door or tape front door shut before lying on its side.)
- 7. Locate and remove the 4 glides at the bottom of the warmer.
- 8. Replace glides with the four, 4 inch legs located in this Kit
- 9. Press the rubber caps found in this kit over the ends of the legs (the legs come with levelers on them, so some adjustment may be necessary for the legs to be even.)
- 10. Tip the unit upright on its newly installed 4 inch legs.
- 11. Replace the water tank and reassemble the water tank cover.
- 12. Reattach the top cap. Be sure the hole in the top cap is over the water fill hole. (If you removed a door in step 6 reassemble it now.)
- 13. Unit is ready for operation.

FS #140071 Rev: 8-24-09